VEDI PRODOTTO

DOCUMENTAZIONE TECNICA

LED ULTRAFLEX FLITSER | R65 6 | LED | 12-24V | AMBER + WIT | ED3794AW



CODICE ARTICOLO

ED3794AW

CARATTERISTICHE

Tensione	12-24v
Grado di protezione	IP69K
Certificazione	CE, ECE-R10, ECE-R65
Garanzia	5 anni

+31 (0)316 372 346
info@tralert.nl
www.tralert.com

Ratio 39 6921 RW Duiven (NL)


COD. ART.


ED3794AW

Tensione	12-24v
Numero di LED	6
Grado di protezione	IP69K
Certificazione	CE, ECE-R10, ECE-R65
Connettore	Estremità libera
Lunghezza cavo	19cm cavo
Montaggio	Montaggio superficiale
Forma	Rettangolare
Dimensioni	112 x 23 x 11mm
Larghezza	112mm
Altezza	23mm


Profondità	11mm
Interasse	105mm
Colore alloggiamento	Nero
Alloggiamento	Syliconen
Colore della lente	Trasparente
Materiale lente	Policarbonato
Garanzia	5 anni
Filtspatronen	69
Soorpatroon	Flitsend, Alternerend, Cruisemode
Waarschuwingslichfunctie	Flitsend, Alternerend, Cruisemode
Waarschuwingslichkleur	Ambra, Bianco


REVISION HISTORY		
REV.	DESCRIPTION	DATE
03	REVISED PER EL0172	2020-10-27
A	INITIAL RELEASE PER EL0172	2020-12-15
B	REVISED PER EL0172	2021-01-14





NO BEZEL





SPECIFICATIONS

1. CERTIFICATIONS: ECE R10; SAE J595 (MAR 2014) CLASS 1; J845 (FEB 2019) CLASS 1S; AMBER(30°), J845 (FEB 2019) CLASS 2S; WHITE(10°); CA Title 13 (SEE CHART) ; ; Reg 65; IP69K / IP67
   Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
2. FLASH MODE: SINGLE : 75 ± 5 FLASHES PER MINUTE
   SINGLE : 375 ± 5 FLASHES PER MINUTE
   DOUBLE : 75 ± 5 FLASHES PER MINUTE
3. VOLTAGE (NOMINAL): 12 to 24 VDC
4. VOLTAGE (EXTREME): 9.0-32 VDC
5. CURRENT (PEAK): SEE CHART(@ 12 VDC NOMINAL)
6. POWER (MAXIMUM): SEE CHART (@ 12 VDC NOMINAL)
7. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
8. CONNECTION: 5-22 AWG WIRES
9. MOUNTING: ADHESIVE OR SCREW MOUNT
10. BASE MATERIAL: SILICONE
11. LENS MATERIAL: SILICONE
12. PRODUCT WEIGHT: 0.07 LBS (0.03 Kg)

FGS. PRODUCT CHART

FGS. NO.	COLOR	POWER (MAX)(W)	CURRENT (A)	SAE J845	CA T13	ECE R65
ED3794AW	AMB/WHT	9.6	0.8	CLASS 1S;AMB(60°)/WHT(40°)	CLASS B; AMB	CLASS 1; AMB
ED3794BA	BLU/AMB	9.8	0.8	CLASS 1S;BLU(60°)/AMB(60°)	CLASS B;BLU, AMB	CLASS 1; BLU, AMB
ED3794BW	BLU/WHT	9.8	0.8	CLASS 1S;BLU(60°)/WHT(40°)	CLASS B; BLU	CLASS 1; BLU
ED3794RA	RED/AMB	9.6	0.8	CLASS 1S;RED(60°)/AMB(60°)	CLASS B; RED,AMB	CLASS 1; RED, AMB
ED3794RB	RED/BLU	9.8	0.8	CLASS 1S;RED(60°)/BLU(60°)	CLASS B; RED,BLU	CLASS 1; RED, BLU
ED3794RW	RED/WHT	8.3	0.6	CLASS 1S; RED(60°)/WHT(40°)	CLASS B; RED	CLASS 1; RED

MOUNTING DISCLAIMER
MOUNTING MEASUREMENT IS FOR REFERENCE ONLY.
MEASURE BEFORE DRILLING.

NOTES:
1. ROHS COMPLIANT
2. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

DISCLAIMER
DIMENSIONS, ILLUSTRATIONS, SPECIFICATIONS AND CERTIFICATIONS CONTAINED IN THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. ECCO ENGINEERING DOES NOT MAINTAIN FORMAL DESIGN CONTROL OF THIS PRODUCT.

PROPRIETARY AND CONFIDENTIAL INFORMATION
THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES, ("ECCO") AND IS ISSUED IN CONFIDENCE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN MAY NOT BE USED, COPIED, REPRODUCED OR OTHERWISE DISCLOSED IN PART OR IN WHOLE TO THIRD PARTIES OR USED FOR ANY OTHER PURPOSE WITHOUT PRIOR ECCO WRITTEN CONSENT. ECCO RESERVES ALL PATENT, COPYRIGHT, TRADEMARK AND OTHER PROPRIETARY RIGHTS TO THIS DOCUMENT, INCLUDING ALL DESIGN, MANUFACTURING, REPRODUCTION, USE AND SALES RIGHTS THERETO. THIS DRAWING IS SUBJECT TO RECALL BY ECCO AT ANY TIME, AND YOUR POSSESSION AND/OR USE CONSTITUTES ACCEPTANCE OF THESE TERMS. ©2020 ELECTRONIC CONTROLS COMPANY

SCALE 1:1
CAD GENERATED DRAWING
DO NOT MANUALLY UPDATE.
MODEL REFERENCED: 01
TOLERANCES ARE IN INCHES. AND MILLIMETERS
TOLERANCES UNLESS OTHERWISE STATED ARE:
MILLIMETERS DECIMALS: XX. ± 1.0mm; XX.X ± 0.5mm
INCHES DECIMALS: X.X ± 0.1; X.XX ± 0.04; X.XXX ± 0.02
ANGLES ± 0.5°
FRACTIONS ± 1/64
THIRD ANGLE PROJECTION

APPROVALS		DATE
DRAWN BY	ABB	2021-01-11
CHECKED	ART	2021-01-12
MECH. ENG.	JLA	2021-01-11
ELEC. ENG.	JES	2021-01-11
TEST ENG.	AL	2021-01-13
SALES.	MD	2021-01-11

Electronically Controlled Use Latest Copy

ECCO www.eccolink.com
Americas (800) 635-5900 | Europe +44 (0)113 237 5340 | Asia Pacific +61 (0)3 63322444

DIR,12LED,SM,FLEXIBLE,DC,12-24V

CUSTOMER PART NO.
SEE CHART

SIZE:	DWG. NO.	REV.
B	ED3794XX	B
SHEET 1 OF 1	Project: EL0172	Date Created: 2020-09-11



CHI È TRALERT®

IL VOSTRO PARTNER SPECIALIZZATO NELL'ILLUMINAZIONE A LED.

TRALERT® si distingue come produttore e rivenditore di illuminazione a LED di qualità per veicoli commerciali, con focus nel settore dei camion e dei rimorchi a 24V. Grazie a un ampio assortimento interamente certificato ECE, a soluzioni su misura e alla consulenza tecnica, TRALERT® supporta i partner B2B in tutta Europa, non soltanto come fornitore, ma dalla progettazione, compresi i cablaggi, fino alla realizzazione e all'assistenza post-vendita.

Le soluzioni di illuminazione TRALERT® garantiscono la massima visibilità per permettere ai Vostri veicoli commerciali di circolare in sicurezza e con un'illuminazione adeguata. I nostri partner si affidano a TRALERT® anche per la garanzia nei tempi di consegna e per la possibilità di personalizzazione, con un costante supporto sul piano marketing e tecnico.







TRALERT®

+31 (0)316 372 346
info@tralert.nl
www.tralert.com
Ratio 39 6921 RW Duiven (NL)