BEKIJK PRODUCT

TECHNISCHE DOCUMENTATIE

LED ULTRAFLEX FLITSER | R65 6 | LED | 12-24V | AMBER + WIT | ED3794AW



ARTIKELNUMMER

ED3794AW

KENMERKEN

Spanning	12-24v
Beschermingsklasse	IP69K
Certificering	CE, ECE-R10, ECE-R65
Garantie	5 jaar

+31 (0)316 372 346
info@tralert.nl
www.tralert.com

Ratio 39 6921 RW Duiven (NL)


ARTIKELNR.


ED3794AW


Spanning	12-24v
Aantal LED's	6
Beschermingsklasse	IP69K
Certificering	CE, ECE-R10, ECE-R65
Aansluiting	Open draadeind
Kabellengte	19cm kabel
Montage	Opbouw
Vorm	Rechthoekig
Afmetingen	112 x 23 x 11mm
Breedte	112mm
Hoogte	23mm

Diepte	11mm
Hart-op-hart	105mm
Behuizingskleur	Zwart
Behuizing	Syliconen
Lenskleur	Transparant
Lensmateriaal	Polycarbonaat
Garantie	5 jaar
Filtspatronen	69
Soorpatroon	Flitsend, Alternerend, Cruisemode
Waarschuwingslichfunctie	Flitsend, Alternerend, Cruisemode
Waarschuwingslichkleur	Amber, Wit

REVISION HISTORY		
REV.	DESCRIPTION	DATE
03	REVISED PER EL0172	2020-10-27
A	INITIAL RELEASE PER EL0172	2020-12-15
B	REVISED PER EL0172	2021-01-14







SPECIFICATIONS

1. CERTIFICATIONS: ECE R10; SAE J595 (MAR 2014) CLASS 1; J845 (FEB 2019) CLASS 1S; AMBER(30°), J845 (FEB 2019) CLASS 2S; WHITE(10°); CA Title 13 (SEE CHART) ; ; Reg 65; IP69K / IP67
   Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
2. FLASH MODE: SINGLE : 75 ± 5 FLASHES PER MINUTE
   SINGLE : 375 ± 5 FLASHES PER MINUTE
   DOUBLE : 75 ± 5 FLASHES PER MINUTE
3. VOLTAGE (NOMINAL): 12 to 24 VDC
4. VOLTAGE (EXTREME): 9.0-32 VDC
5. CURRENT (PEAK): SEE CHART(@ 12 VDC NOMINAL)
6. POWER (MAXIMUM): SEE CHART (@ 12 VDC NOMINAL)
7. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
8. CONNECTION: 5-22 AWG WIRES
9. MOUNTING: ADHESIVE OR SCREW MOUNT
10. BASE MATERIAL: SILICONE
11. LENS MATERIAL: SILICONE
12. PRODUCT WEIGHT: 0.07 LBS (0.03 Kg)

FGS. PRODUCT CHART

FGS. NO.	COLOR	POWER (MAX)(W)	CURRENT (A)	SAE J845	CA T13	ECE R65
ED3794AW	AMB/WHT	9.6	0.8	CLASS 1S;AMB(60°)/WHT(40°)	CLASS B; AMB	CLASS 1; AMB
ED3794BA	BLU/AMB	9.8	0.8	CLASS 1S;BLU(60°)/AMB(60°)	CLASS B;BLU, AMB	CLASS 1; BLU, AMB
ED3794BW	BLU/WHT	9.8	0.8	CLASS 1S;BLU(60°)/WHT(40°)	CLASS B; BLU	CLASS 1; BLU
ED3794RA	RED/AMB	9.6	0.8	CLASS 1S;RED(60°)/AMB(60°)	CLASS B; RED,AMB	CLASS 1; RED, AMB
ED3794RB	RED/BLU	9.8	0.8	CLASS 1S;RED(60°)/BLU(60°)	CLASS B; RED,BLU	CLASS 1; RED, BLU
ED3794RW	RED/WHT	8.3	0.6	CLASS 1S; RED(60°)/WHT(40°)	CLASS B; RED	CLASS 1; RED

MOUNTING DISCLAIMER
MOUNTING MEASUREMENT IS FOR REFERENCE ONLY.
MEASURE BEFORE DRILLING.

NOTES:
1. ROHS COMPLIANT
2. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

DISCLAIMER
DIMENSIONS, ILLUSTRATIONS, SPECIFICATIONS AND CERTIFICATIONS CONTAINED IN THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. ECCO ENGINEERING DOES NOT MAINTAIN FORMAL DESIGN CONTROL OF THIS PRODUCT.

PROPRIETARY AND CONFIDENTIAL INFORMATION
THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES, ("ECCO") AND IS ISSUED IN CONFIDENCE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN MAY NOT BE USED, COPIED, REPRODUCED OR OTHERWISE DISCLOSED IN PART OR IN WHOLE TO THIRD PARTIES OR USED FOR ANY OTHER PURPOSE WITHOUT PRIOR ECCO WRITTEN CONSENT. ECCO RESERVES ALL PATENT, COPYRIGHT, TRADEMARK AND OTHER PROPRIETARY RIGHTS TO THIS DOCUMENT, INCLUDING ALL DESIGN, MANUFACTURING, REPRODUCTION, USE AND SALES RIGHTS THERETO. THIS DRAWING IS SUBJECT TO RECALL BY ECCO AT ANY TIME, AND YOUR POSSESSION AND/OR USE CONSTITUTES ACCEPTANCE OF THESE TERMS. ©2020 ELECTRONIC CONTROLS COMPANY

SCALE 1:1
CAD GENERATED DRAWING
DO NOT MANUALLY UPDATE.
MODEL REFERENCED: 01
TOLERANCES ARE IN INCHES, AND MILLIMETERS
TOLERANCES UNLESS OTHERWISE STATED ARE:
MILLIMETERS DECIMALS: XX. ± 1.0mm, XX.X ± 0.5mm
INCHES DECIMALS: X.X ± 0.1, X.XX ± 0.04, X.XXX ± 0.02
ANGLES ± 0.5°
FRACTIONS ± 1/64
THIRD ANGLE PROJECTION

APPROVALS		DATE
DRAWN BY	ABB	2021-01-11
CHECKED	ART	2021-01-12
MECH. ENG.	JLA	2021-01-11
ELEC. ENG.	JES	2021-01-11
TEST ENG.	AL	2021-01-13
SALES.	MD	2021-01-11

Electronically Controlled Use Latest Copy

ECCO www.eccolink.com
Americas (800) 635-5900 | Europe +44 (0)113 237 5340 | Asia Pacific +61 (0)3 63322444

DIR,12LED,SM,FLEXIBLE,DC,12-24V

CUSTOMER PART NO.
SEE CHART

SIZE:	DWG. NO.	REV.
B	ED3794XX	B
SHEET 1 OF 1	Project: EL0172	Date Created: 2020-09-11



OVER TRALERT®

UW PARTNER IN LED-VERLICHTING VOOR COMMERCIËLE VOERTUIGEN.

TRALERT® is dé Europese producent en leverancier van hoogwaardige LED-verlichting voor commerciële voertuigen, primair gericht op de 24V truck- en trailerwereld. Middels een breed, volledig ECE-gecertificeerd assortiment, maatwerkoplossingen en directe leveringen ondersteunt TRALERT® haar B2B-partners door heel Europa. TRALERT® opereert niet slechts als leverancier, maar als een kennispartner die de complete LED-verlichtingsoplossingen biedt: van ontwerp inclusief kabelsets tot realisatie en ondersteuning.

Verlichtingsoplossingen van TRALERT® zorgen voor optimale zichtbaarheid en betrouwbaarheid, zodat uw commerciële voertuigen veilig en goed verlicht de weg op kunnen. Als betrokken partner helpt TRALERT® haar partners verder dan levering alleen: met samenwerking die waarde toevoegt en resultaat oplevert.







TRALERT®

+31 (0)316 372 346
info@tralert.nl
www.tralert.com
Ratio 39 6921 RW Duiven (NL)