

**Voltage Range:** 12/24V**Warranty:** 5 years**Ingress Protection:** IP67**Approval:** ECE & EMC ✓

- 80mm square lamp modules
- Quad surface mounting bracket
- Tough polycarbonate lenses
- Shock, water & dust proof

- Replacement lamp modules available; 80AMEB, 80RMEB, 80WMEB, 80FMEB
- Harness system compatible (80BFWARME only)

**STOP / TAIL / INDICATOR / REVERSE****80BRRAWME***Current Draw (13.8V / 28V):**Stop: 0.33A / 0.25A, Tail: 0.06A / 0.04A, Indicator: 0.29A / 0.22A, Reverse: 0.17A / 0.21A***STOP / TAIL / INDICATOR / FOG****80BFARRME***Current Draw (13.8V / 28V):**Stop: 0.33A / 0.25A, Tail: 0.06A / 0.04A, Indicator: 0.29A / 0.22A, Fog: 0.42A / 0.21A***STOP / TAIL / INDICATOR / REVERSE / FOG****80BFWARME***Current Draw (13.8V / 28V):**Stop: 0.33A / 0.25A, Tail: 0.06A / 0.04A, Indicator: 0.29A / 0.22A, Reverse: 0.17A / 0.21A, Fog: 0.42A / 0.21A***STOP / TAIL / INDICATOR****80BAARRME***Current Draw (13.8V / 28V):**Stop: 0.33A / 0.25A, Tail: 0.06A / 0.04A, Indicator: 0.29A / 0.22A*

Overall Size: 350 x 105 x 47mm  
Cable Length: 400mm

