

## LD 3110/P

### MARKER LIGHT

**LD 3110/P** is a triple marker lamp that comes with a flexible hanger and compact dimensions. It is specifically designed for mounting **on the right side of the vehicles**, ranging from small trailers to trucks and trailers. The lamp emits a bright light and fulfills the most important functions. **Lamp functions:** - front marker light (white light color) - side position light (orange light color) - rear marker light (red light color) The lamp operates on a universal voltage of **12/24 V** and is characterized by low power consumption. Only branded diodes are used for the production of the **lamp with reflector**, which definitely distinguish the quality of lighting and attractively emphasize the outline of a moving vehicle. Product is fully hermetic (ingress protection rating **IP 68**), and the operating temperature range is **from -30 degrees C to +50 degrees C. Ensure your safety on the road! Identify your vehicle with LED new arrivals by Horpol!**

### DANE TECHNICZNE

|                           |                             |                                             |
|---------------------------|-----------------------------|---------------------------------------------|
| Light group               | LED quantity                | Light category                              |
| HOR 77A                   | 4                           | marker                                      |
| Supply voltage            | Front clearance light       | Power rating                                |
| 12/24 V                   | yes                         | 0,7/1,4 W                                   |
| Rear clearance light      | Operating temperature range | Cable                                       |
| yes                       | from -30°C to +50°C         | 2×0,75 mm <sup>2</sup> ; cable length 0,6 m |
| Side marker light         | Side                        | LED light                                   |
| yes                       | right                       | yes                                         |
| Ingress protection rating |                             |                                             |
| IP 68                     |                             |                                             |

