











## **Specifications**

Article number	SL5-1359A
Voltage range	12-24 Volt
Dimensions	1359 x 203.2 x 25.5mm
Height incl. bracket	65.5mm
Controller dimensions	120.5 x 73.5 x 18mm
Controller connection	Wireless, rechargeable with USB-C
Light colour	Amber
LED modules	22 modules
Number of flash patterns	18
IP value	IP67
Certificates	CE, ECE R10, ECE R65 TA2, CISPR25 CL3
Controller	Including
T (C: 1 :	
Traffic advisors	Including
Traffic advisors  Search light / work light	Including  Excluding
Search light / work light	Excluding
Search light / work light Rear light modules	Excluding Excluding
Search light / work light Rear light modules Cruise mode	Excluding Excluding Including
Search light / work light Rear light modules Cruise mode Dimming function	Excluding Excluding Including Including
Search light / work light Rear light modules Cruise mode Dimming function Work temperarture	Excluding Excluding Including Including -40°C to 65°C
Search light / work light Rear light modules Cruise mode Dimming function Work temperarture Lens material	Excluding Excluding Including Including -40°C to 65°C Polycarbonate (dark-look)
Search light / work light Rear light modules Cruise mode Dimming function Work temperarture Lens material Housing material	Excluding Excluding Including Including -40°C to 65°C Polycarbonate (dark-look) Aluminium

